

## Specifications

- Six to Ten person pump
- Open drip-proof motor drive
- Oil-less – eliminates OSHA required CO monitors, temperature alarms, airline filters
- Electric Driven Pump
- Made in the USA
- Portable
- Capacity to supply air to:
  - Seven hood-style; or
  - Ten half or full face mask airline respirators
- Shipped complete with
  - Inlet and outlet filter cartridges
  - Pressure gauges
  - Pressure relief valves
  - Two air supply hose quick-disconnect pods with six 1/2" Industrial Interchange (Hansen compatible) quick-disconnect couplers.
- Carbon vans are replaceable and need no adjustment, lasting for 3,000 – 10,000 operational hours if properly maintained.
- Three Phase motor standard
- Protective reversing starters standard on all three phase motors
- Weighs 317 lbs
- Dimensions: 26" wide x 38" long x 32" high
- Maximum air pressure of 15psig
- Air flow of 50 CFM at 10 psig
- Air supply hose quick-disconnect pod can be extended 300 feet from the pump
- Tire pressure of 50 psig max
- Can be custom built to customer specification

## Electrical Motor Options

- Single Phase 5 HP Motor, 208V or 230V
- Three Phase 5 HP Motor, Reversing Starter, 208/230/460V
- Three Phase 7.5 HP Motor, Reversing Starter, 208/230/460 V

## Filters

- Breathable air inlet can be located up to 300 feet away from the pump
- Medium efficiency Inlet Filter (particulates large than 25 microns filtered out of the air supply). Replace after 500 operational hours or less depending on working conditions.
- Outlet filter is Carbofine with activated carbon. Replace after 200 operational hours or less depending on working conditions.

## Respirator Capabilities

- May be used in conjunction with any manufacture's supplied air respirators. Check the respirator's owner's manual to verify that the cfm output of the pump is adequate.
- Hood-style respirators require a minimum of 6 cfm each and 12-15 cfm each when used with a cool tube
- Half and full face style respirators require a minimum of 4 cfm each

## Warranty

1 year limited warranty to original purchaser from date of purchase

**Americas:**  
**E.D. Bullard Company**  
1898 Safety Way  
Cynthiana, KY 41031-9303  
Toll free: 877-BULLARD (285-5273)  
Tel: 859-234-6616  
Fax: 859-234-8987  
[www.bullard.com](http://www.bullard.com)

**Europe:**  
**Bullard GmbH**  
Lilienthalstrasse 12  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax : +49-2642 9999829  
[www.bullardextrem.com](http://www.bullardextrem.com)

**Asia-Pacific:**  
**Bullard Asia Pacific Pte. Ltd.**  
LHK Building  
701, Sims Drive, #04-03  
Singapore 387383  
Tel: +65-6745-0556  
Fax: +65-6745-5176  
[www.bullard.com](http://www.bullard.com)



©2011 Bullard. All rights reserved.