

Specifications

- Capacity to supply one NIOSH-approved respirator
- Portable – Includes roll cage and wheel kit (standard)
- Oil-less* – eliminates OSHA-required CO monitors, temperature alarms, and airline filters
 - * Compressor does contain lubricated motor bearings and rod bearings. The bearings are a sealed design and lubricated for the life of the product. They are also located outside the compressed (wetted) air path of the compressor, eliminating any potential lubrication leakage inside the air path.
- 2.0 HP, electric-driven
- 6 ft. 110 V cord with NEMA 5-20 three-pronged plug
- Liquid-filled pressure gauge (0-100 psig)
- 1/2" Industrial Interchange (Hansen compatible) quick-disconnect coupler
 - At least 100' of 1/2" ID breathing air supply hose is required for proper performance
- Weight: 100 lbs. (45.4 kg)
Shipping weight: 185 lbs. (83.9 kg)
- Sound Level (dBA) at:
 - 1 ft. – 96.4
 - 6 ft. – 88.8
 - 10 ft. – 84.6
 - 15 ft. – 80.6
- Air flow of 8 cfm at 60 psig (225 lpm @ 400 kPa)
- Dimensions: 28" L x 18" W X 20.5" H
Shipping Dimensions: 48" L x 32" W X 35.5" H
- Maximum Outlet Air pressure of 60 psig (400 kPa)
- Does not need to be bolted down
- No calibration required
- Made in the USA



Electrical Motor Specifications

- Open, drip-proof enclosure
- Meets UL requirements
- CSA approved
- 2.0 HP
- Single Phase
- 60 Hz cycle
- 115 Volts
- 19 amps @ 115 V
- 1.25 Service Factor
- Internal Thermal Overload

Filters

- Breathable air inlets (4) can be located up to 300 feet away from pump
- Medium Efficiency Inlet Filters (particulates larger than 25 microns filtered out of the air supply). Replace after 500 operational hours or less depending on working conditions
- 90-micron Inline Outlet Filter. Replace after 500 operational hours or less depending on working conditions

Respirator Capabilities

- May be used in conjunction with any manufacturer's NIOSH-approved supplied air respirators. Check the respirator's owner's manual to verify pressure and CFM requirements.

Warranty

- 1-year limited warranty to original purchaser from date of purchase

Americas:
Bullard
1898 Safety Way
Cynthiana, KY 41031-9303
Toll free: 877-BULLARD (285-5273)
Tel: 859-234-6616
Fax: 859-234-8987

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax : +49-2642 9999829

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176



©2014 Bullard. All rights reserved.