



Head
Protection



Respiratory
Protection



Fire and Rescue
Safety



Thermal
Imaging

Now... Incident Command and Control ... In the palm of your hand

The MobileLink Handheld Receiver revolutionizes thermal imaging command operations.

Finally, a compact, easy-to-use handheld receiver that fits the needs of every incident commander. Designed as the ultimate in mobility, MobileLink enables remote monitoring of transmitted TACSIGHT thermal imaging video. With the push of a single button, the MobileLink is ready to go wherever the action demands.

- Crystal-Clear 3.5" display
- Uses standard T3 model batteries
- Handheld design with adjustable hand strap
- Two or four channel availability
- Durable Ultem[®] thermoplastic housing
- BNC Video-out jack
(RCA adapter included)



You CAN take it with you!

MobileLink joins the Bullard line of support products designed to maximize your department's utilization of the TACSIGHT Thermal Imager. With its versatile design using no cords or bulky antennas, the battery operated receiver allows the user to remotely monitor the scene from distances up to 300 feet through typical construction, and further in outdoor environments.

Multiple Channel Capability

To ensure compatibility with TACSIGHT thermal imagers, MobileLink is available in either two or four channel versions, enabling incident commanders the ability to monitor multiple thermal imagers at a scene.

Built BULLARD TOUGH

Bullard's MobileLink is housed in a tough, Ultem engineered polymer, and is water resistant to endure the rigors of law enforcement. MobileLink operates for over two hours using the same battery that powers the TACSIGHT. Users can send video to a recording device through MobileLink's video out jack.

MobileLink Receiver Specifications

Television systems	NTSC/PAL selectable
Relative humidity	10% to 90%
Power requirement.....	TACSIGHT NiMH Battery
Power Input	TACSIGHT NiMH Battery
Dimensions.....	6" high, 4.25" wide, 4.5" deep (not including antenna or hand strap, but with battery installed) (antenna adds 3.5" to height)
Weight.....	1.9 lbs. (30.4 ounces, 863 g) with strap and battery, 1.28 lbs. (20.5 ounces, 581 g) without battery
Receiving Frequency (2 CH)	2.458 GHz or 2.474 GHz
Receiving Frequency (4 CH)	2.456 GHz, 2.463 GHz, 2.470 GHz, or 2.477 GHz
Video Outputs (BNC)	75-ohm 1-Volt P-P



Bullard
1898 Safety Way
Cynthiana, KY 41031-9303
Toll free: +877-BULLARD (285-5273)
Tel: +859-234-6616
Fax: +859-234-8987
www.bullard.com

Bullard GmbH
Hochkreuzallee 36
53175 Bonn-Bad Godesberg
Germany
Tel: +49 228 931933 0
Fax: +49 228 931933 50
www.bullardextrem.com



©2004 Bullard. All rights reserved.
Bullard is a registered trademark of Bullard.
"It's your life and you're worth it", MobileLink and TACSIGHT are trademarks of Bullard.
Ultem is a registered trademark of General Electric.
8135 (0904)