

SceneCatcher™

Version 2.0

SceneCatcher provides law enforcement officers the technology and capability needed for recording and storing vital thermal imaging video and still images. Now, with capacity to record five hours of video and hundreds of still images, SceneCatcher 2.0 documents everything you need during incidents and investigations.

Version 2.0

- 5X recording time
- Higher video and image resolution and performance
- Faster file transfers
- Improved PC Interface

The higher resolution imagery and faster frame rates add up to an even more lifelike viewing experience, plus files transfer to your PC quicker than ever with updated, USB 2.0 technology. The convenient mini-USB to USB connection and Plug and Play interface means no complicated hardware configuration and software installation. *

See the Action

- Housed in a rugged handle
- Mounts easily on TacSight S2 and SE35 thermal imagers

Record the Footage

- Capture images or video while transmitting wireless video
- Capture five hours of video and hundreds of still images

Take it with You

- Download images and video easily through a USB connection
- Optional transmitter transmits up to 600 feet



Record up to five hours of video



Capture hundreds of high quality still images

* No separate viewer software required. Images and videos can be viewed using programs such as Windows® Picture and Fax Viewer and Windows® Media Player

**TRANSMITS AND
RECORDS AT
THE SAME TIME!**



www.bullard.com

SceneCatcher™

Technical Specifications

The innovative SceneCatcher enables law enforcement officers to take both snapshots and video of the images they see on their Bullard TacSight Thermal Imagers. This new tool is ideal for use in analysis and records of evidence. For use as a standalone device or coupled with a Bullard transmitter, SceneCatcher allows you to archive incidents in full detail. The unit mounts easily onto Bullard TacSight Thermal Imagers.

SceneCatcher Technical Specifications

Video format: NTSC
Video file type: AVI
Video image size: 640 x 480
Video record time: 5 hours

Still image export: JPEG
Still image resolution: 640 x 480
Still image capacity: 300 images*
Connection: mini-USB to USB

Transmitter Technical Specifications

Mounting: External
Antenna Type: Dipole
Power Output: 750 mW
Power Consumption: 2.6 W
Nominal Range: 600 feet (through typical frame construction)

Signal Type: Analog
Transmitting Frequency: 2.4 GHz
Power Supply: Internal
FCC License: Part 90

* While storing 5 hours of video: can store 80,000 images without video



NOTE

SceneCatcher is housed in a handle, which can also include a transmitter. With the optional two-channel transmitter, users can record images and video and simultaneously transmit to one or more receiving devices, such as the Bullard MobileLink handheld receiver or the Mobile Command Center. Already using a Bullard transmitter? You can upgrade your transmitter handle to include the SceneCatcher.

Americas:
E.D. Bullard Company
1898 Safety Way • Cynthiana, KY 41031-9303
Toll free: 877-BULLARD (285-5273)
Tel: 859-234-6616 • Fax: 859-234-8987
www.bullard.com

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980 • Fax: +49-2642 9999829
www.bullardextrem.com

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03 • Singapore 387383
Tel: +65-6745-0556 • Fax: +65-6745-5176
www.bullard.com

©2010 Bullard. All rights reserved.

SceneCatcher and MobileLink are trademarks of Bullard.
Kevlar and Neoprene are registered trademarks of E.I. DuPont de Nemours & Company.

Ultim is a registered trademark of General Electric.

