



Installation of GVXCP Cheek Pads

To install the 88VX cheek pads, follow the steps below:

1. Remove inner plenum shell by pulling up on the yellow tab in the back of the helmet (Figure 1).
2. Take one Velcro® strip. Start by adhering Velcro on the beveled edge of the front of the 88VX helmet. The Velcro should start approximately 1 1/2" beyond the green gasket. Repeat on opposite side with second Velcro Strip (Figure 2).
3. Replace inner plenum shell.

Change Size of GVXCP Cheek Pads

To change the size of the 88VX cheek pads, follow the steps below:

1. Remove cheek pads from the helmet.
2. Open top flap on flat edge of cheek pad.
3. Leave both foam pads for the tightest fit, remove one foam pad for a less tight fit, or remove all foam padding for the loosest fit (Figure 3).
4. Close cheek pad, once sized, by adhering Velcro flap to inner flat edge.
5. Secure cheek pad to helmet with flat edge at the bottom of the 88VX helmet.

Inspection of GVXCP Cheek Pads

Be sure the cheek pads are fastened securely to the Velcro in the helmet, clear of any dirt and debris prior to donning the cap.

Cleaning the GVXCP Cheek Pads

The optional cheek pads can be wiped with mild detergent or machine washed in warm water on a gentle cycle and let air dry.

Figure 1




Figure 2





Figure 3





GVXCP Cheek Pads for 88VX



Americas:
Bullard
1898 Safety Way
Cynthiana, KY 41031-9303 • USA
Toll-free within USA:
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Asia Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176

©2012 Bullard. All rights reserved.
Velcro is a registered trademark of
Velcro USA.

6082009964A (0812)