



CC20LF Series Loose Fitting Facepieces Bid Specifications

Respirator Type Supplied Air Respirators (SAR) or Powered Air Purifying Respirators (PAPR)

Approvals

- The loose fitting facepiece shall be approved and certified by the National Institute for Occupational Safety and Health (NIOSH) as a component of a Type C continuous-flow class supplied air respirator (SAR) and/or as a component of a powered air purifying respirator (PAPR) under the Code of Federal Regulations (42 CFR 84) requirements.

Loose-Fitting Facepiece

- Sewn- in suspension
- Latex-free
- Quick-attach twist lock connection color coded to indicate facepiece size
- No fit test required
- Accommodates beards, hearing protection, prescription eyewear or safety glasses
- NIOSH Approved for use as a component of a PAPR
- Made out of Dupont Tychem® QC
- Chemically resistant PETG lens
- Soft plenum over-the-top air delivery system

Breathing Tube Assembly

- Approved and available in 3 different lengths
- Approved and available with constant or adjustable flow control device with 1/2" Industrial Interchange (Hansen compatible) quick disconnect coupler for ambient air pumps.
- Approved and available with constant or adjustable flow control device with 1/4" quick disconnect coupler for compressed air with the following choices of fittings:
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader
 - CEJN
 - Bayonet
- Standard Nylon belt or optional Decontamination belt
- Available with 3 different breathing tube covers made of Tychem® QC, Tychem® SL or clear Poly

Airline Supply Hose

- NIOSH approved for use with 25-300 feet of airline supply hose for compressed air.
- NIOSH approved for use with 50-300 feet of airline supply hose for ambient air pumps.
- Choice of EPDM reinforced rubber 3/8" I.D. hose or nylon coiled hose for compressed air, or 1/2" ID hose for ambient air pumps.
- Manufactured specifically to carry breathing air.
- Offers 1/2" industrial interchange (Hansen compatible) nipple for ambient air pumps
- Approved and available with the following quick disconnect couplers compatible with breathing tube fittings for compressed air compatible with Bullard breathing tube fittings:
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader
 - CEJN
 - Bayonet



CC20LF Series Loose Fitting Facepieces Bid Specifications

Optional Climate Control

- NIOSH approved for use with Bullard's CC20LF series
- Cool tube (AC1000) – Compressed air only
 - Frigatron 2000 – NIOSH approved use with Bullard Free-air pumps ADP20 and EDP30.
 - Cools incoming air by as much as 30 F (17 C)
 - Adjustable airflow control valve for individual comfort
- Hot/Cold Tube (HC2400) – Compressed air only
 - Cools or warms incoming air by as much as 30 F (17 C)
 - Adjustable airflow control valve for individual comfort
 - Change between cooled or warmed air in seconds
- Dual-Cool (DC5040) – Compressed air only
 - Cools incoming air by as much as 30 F (17 C).
 - Cools air supplied to both hood and cooling vest
 - Separate control knobs allow adjustment of the temperature of air to each zone
 - Compressor must have the capacity to supply a minimum of 30 cfm (850lpm) of air
- Cooling Vest (DC70)
 - Sizes M, L, XL, XXL
 - Can be used without respirator

Warranty

- 1 year limited manufacturer warranty for original purchaser from date of purchase.

Americas:
E.D. Bullard Company
1898 Safety Way
Cynthiana, KY 41031-9303
Toll free: 877-BULLARD (285-5273)
Tel: 859-234-6616
Fax: 859-234-8987
www.bullard.com

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax : +49-2642 9999829
www.bullardextrem.com

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176
www.bullard.com

©2011 Bullard. All rights reserved.

